

In the Claims

Claims 1-20 are pending in this application with claims 1, 2, 6, 7, 14, 16, 18, 19 and 20 being amended by this response

1. (Currently Amended) A system for use by individual processing devices of a group of networked processing devices, for managing operational failure occurrences in devices of said group, comprising:

an interface processor for maintaining transition information identifying a second processing device for taking over execution of tasks of a first processing device in response to an operational failure of said first processing device and for dynamically updating said transition information in response to a change in ~~transition information~~ utilization parameters occurring in another processing device of said group;

an operation detector for detecting an operational failure of said first processing device; and

a failure controller for initiating execution, by said second processing device, of tasks designated to be performed by said first processing device in response to detection of an operational failure of said first processing device.

2. (Currently Amended) A system according to claim 1, wherein

said utilization parameters identify utilization of resources including at least one of, (a) memory, (b) CPU and (c) input-output communication, used for performing particular computer operation tasks in normal operation,

each individual processing device of said group of networked processing devices incorporates a repository storing transition information, and

said individual processing devices are in communication to maintain consistent transition information in said individual processing devices.

3. (Original) A system according to claim 1, wherein

said transition information comprises a prioritized list of processing devices for assuming execution of tasks of a first processing device in response to an operational failure of said first processing device and

said prioritized list is dynamically updated in response to

communication from another processing device of said group.

4. (Original) A system according to claim 3, wherein
said prioritized list indicates passive non-operational processing devices for assuming execution of tasks of a first processing device in response to an operational failure of said first processing device.

5. (Original) A system according to claim 3, wherein
said prioritized list is dynamically updated in response to a plurality of factors including at least one of, (a) detection of an operational failure of another processing device in said group and (b) detection of available memory of another processing device of said group being below a predetermined threshold.

6. (Currently Amended) A system ~~according to claim 5,~~
for use by individual processing devices of a group of networked processing devices,
for managing operational failure occurrences in devices of said group, comprising:

an interface processor for maintaining transition information
identifying a second processing device for taking over execution of tasks of a first
processing device in response to an operational failure of said first processing device
and for updating said transition information in response to a change in transition
information occurring in another processing device of said group;

an operation detector for detecting an operational failure of said first
processing device; and

a failure controller for initiating execution, by said second processing
device, of tasks designated to be performed by said first processing device in response
to detection of an operational failure of said first processing device wherein

said prioritized list is dynamically updated in response to a plurality of
factors including at least one of, (a) detection of an operational failure of another
processing device in said group, (b) detection of available memory of another
processing device of said group being below a predetermined threshold, and

~~said plurality of factors including at least one of, (a)~~ (c) detection of operational load
of another processing device in said group exceeding a predetermined threshold, (b)
(d) detection of use of CPU (Central Processing Unit) resources of another processing

device of said group exceeding a predetermined threshold and ~~(e)~~ (e) detection of a number of I/O (input – output) operations, in a predetermined time period, of another processing device of said group exceeding a predetermined threshold.

7. (Currently Amended) A system according to claim 3, wherein said prioritized list is dynamically updated ~~in~~ to include state information indicating at least one of, (a) a detected change of state of another processing device of said group from available to unavailable and (b) a detected change of state of another processing device of said group from unavailable to available.

8. (Original) A system according to claim 7, including said interface processor determines a state of a processing device of said group from state information provided by a different processing device of said group.

9. (Original) A system according to claim 1, including said interface processor interrogates other processing devices of said group to identify a change in transition information occurring in another processing device of said group.

10. (Original) A system according to claim 1, wherein an operational failure of a processing device comprises at least one of, (a) a software execution failure and (b) a hardware failure.

11. (Original) A system according to claim 1, wherein a processing device comprises at least one of, (a) server, (b) a computer, (c) a PC, (d) a PDA, (e) a telephone, (f) a processing device communicating via wireless communication, (g) a television, (h) a set top box and (i) a networking device, including executable software.

12. (Original) A system according to claim 1, wherein

an individual processing device of said group incorporates similar software to other processing devices of said group.

13. (Original) A system according to claim 1, wherein
said group comprises a cluster and a processing device comprises a node.

14. (Currently Amended) A system for use by individual processing devices of a group of networked processing devices, for managing operational failure occurrences in devices of said group, comprising:

an individual processing device including,

a repository including transition information identifying a second processing device for taking over execution of tasks designated to be performed by a first processing device in response to an operational failure of said first processing device;

an interface processor for maintaining and updating said transition information in response to a change in ~~transition information~~ utilization parameters occurring in another processing device of said group;

an operation detector for detecting an operational failure of said first processing device; and

a failure controller for initiating execution, by said second processing device, of tasks designated to be performed by said first processing device in response to detection of an operational failure of said first processing device.

15. (Original) A system according to claim 14, wherein
said interface processor communicates with other processing devices of said group to maintain consistent transition information in said individual processing device transition information repositories.

16. (Currently Amended) A system for use by individual processing devices of a group of networked processing devices, for managing operational failure occurrences in devices of said group, comprising:

an individual processing device including,

a repository including transition information identifying a second currently non-operational processing device for taking over execution of tasks designated to be performed by a first processing device in response to an operational failure of said first processing device;

an interface processor for maintaining and updating said transition information in response to a change in utilization parameters of another processing device in said group and at least one of, (a) detection of an operational failure of another processing device in said group and (b) detection of available memory of another processing device of said group being below a predetermined threshold;

an operation detector for detecting an operational failure of said first processing device; and

a failure controller for initiating execution, by said second processing device, of tasks designated to be performed by said first processing device in response to detection of an operational failure of said first processing device.

17. (Original) A system according to claim 16, wherein

said transition information comprises a prioritized list of processing devices for assuming execution of tasks designated to be performed by said first processing device in response to an operational failure of said first processing device and

said prioritized list is dynamically updated in response to communication from another processing device of said group

18. (Currently Amended) A method for use by individual processing devices of a group of networked processing devices, for managing operational failure occurrences in devices of said group, comprising the activities of:

maintaining transition information identifying a second processing device for taking over execution of tasks of a first processing device in response to an operational failure of said first processing device and for updating said transition information in response to a change in utilization parameters identifying utilization of resources in another processing device of said group including of at least one of, (a) memory, (b) CPU and (c) input-output communication, used for performing particular computer operation tasks in normal operation ~~in response to a change in transition information occurring in another processing device of said group;~~

detecting an operational failure of said first processing device; and

initiating execution, by said second processing device, of tasks designated to be performed by said first processing device in response to detection of an operational failure of said first processing device.

19. (Currently Amended) A method for use by individual processing devices of a group of networked processing devices, for managing operational failure occurrences in devices of said group, comprising the activities of:

storing transition information identifying a second processing device for taking over execution of tasks designated to be performed by a first processing device in response to an operational failure of said first processing device;

maintaining and updating said transition information indicating a change in utilization parameters identifying utilization of resources including of at least one of, (a) memory, (b) CPU (c) input-output communication and (d) processing devices, used for performing particular computer operation tasks in normal operation, ~~in response to a change in transition information occurring~~ in another processing device of said group;

detecting an operational failure of said first processing device; and

initiating execution, by said second processing device, of tasks designated to be performed by said first processing device in response to detection of an operational failure of said first processing device.

20. (Currently Amended) A method for use by individual processing devices of a group of networked processing devices, for managing operational failure occurrences in devices of said group, comprising the activities of:

maintaining transition information indicating a change in utilization parameters identifying a second currently non-operational processing device for taking over execution of tasks designated to be performed by a first processing device in response to an operational failure of said first processing device;

updating said transition information in response to a change in utilization parameters of another processing device in said group and at least one of, (a) detection of an operational failure of another processing device in said group and (b) detection of available memory of another processing device of said group being below a predetermined threshold;

detecting an operational failure of said first processing device; and

initiating execution, by said second processing device, of tasks designated to be performed by said first processing device in response to detection of an operational failure of said first processing device.